

DFT-BASED STUDY OF STRUCTURAL, ELECTRONIC AND MULTIFUNCTIONAL PROPERTIES OF METAL OXIDE NANOMATERIALS FOR ENERGY APPLICATIONS

***Musa Khan¹, Tawsif Ahmad², Moneeb Ahmad³, Waqar Ahmad⁴**

^{1, 2, 3, 4}Department of Physics, Govt. Post Graduate College Timergara, Dir Lower, Pakistan

Affiliated with University of Malakand

***Corresponding Author:** (musa0hamdard@gmail.com)

DOI : (<https://doi.org/10.71146/kjmr6667>)

Article Info

Abstract



This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license

<https://creativecommons.org/licenses/by/4.0>

Metal oxide nanomaterials are among the most important functional materials for modern energy-storage and energy-conversion technologies. Their usefulness originates from the wide range of crystal structures, oxidation states, surface chemistries, electronic configurations, optical responses, catalytic activities and defect-dependent properties that can be achieved by changing composition and nanoscale architecture. Density Functional Theory (DFT) provides an atomistic framework for understanding these properties before or alongside experimental synthesis. A carefully designed DFT study can determine optimized structural parameters, formation and binding energies, electronic band structures, band gaps, density of states, projected density of states, charge transfer, chemical bonding, work functions, optical and dielectric functions, magnetic moments, mechanical properties, phonon stability, surface energies, adsorption energies, ion-diffusion barriers and reaction energetics. These descriptors are directly connected to battery electrodes, supercapacitors, photocatalysts, electrocatalysts, fuel cells, hydrogen production, carbon-dioxide conversion and solar-energy devices. This article presents an extended computational framework for metal oxide nanomaterials, emphasizing how each calculated property should be interpreted and how graphical outputs can be used to build a scientifically meaningful results section. Particular attention is given to oxygen vacancies, substitutional doping, strain and heterostructures because these approaches can modify charge transport, band alignment, surface reactivity and ion mobility. The graphs included in this document are explicitly illustrative schematics rather than fabricated first-principles results. For a publication or thesis, they should be replaced by plots generated from the actual DFT output of a specified material and computational setup.

Keywords:

Density Functional Theory; metal oxide nanomaterials; energy storage; energy conversion; structural properties; electronic structure; band gap; DOS; PDOS; chemical bonding; charge transfer; optical properties; dielectric response; work function; surface energy; adsorption; ion diffusion; magnetic properties; mechanical properties; phonons; defects; oxygen vacancies; catalysis.

1. Introduction

The transition toward sustainable energy requires materials that can efficiently store, transport and convert energy while remaining chemically and mechanically stable. Rechargeable batteries, supercapacitors, fuel cells, solar cells, photocatalytic water splitting and carbon-dioxide conversion all depend on materials with carefully balanced combinations of electronic, ionic, optical, catalytic and structural properties. Metal oxides occupy an important position in this field because oxygen can form stable compounds with many metallic elements and because the resulting materials can display metallic, semiconducting, insulating, magnetic, dielectric, photoactive and redox-active behavior. Examples include TiO_2 , ZnO , Fe_2O_3 , Fe_3O_4 , CeO_2 , MnO_2 , NiO , Co_3O_4 , V_2O_5 , MoO_3 and WO_3 .

Nanostructuring further expands the design space. When an oxide is reduced to nanoparticles, nanowires, nanosheets, porous particles or other nanoscale morphologies, the fraction of atoms located at surfaces and interfaces increases. Surface atoms have lower coordination than bulk atoms and can therefore possess different bond lengths, charge distributions and chemical reactivity. Nanoscale materials may also provide shorter pathways for ion transport and larger electrochemically active areas. However, nanosizing can introduce additional defects, strain, reconstruction and interface effects, so it is not sufficient to discuss only the bulk crystal structure.

DFT is valuable because it links these macroscopic observations to atomic-scale mechanisms. The Hohenberg-Kohn framework establishes that the ground-state properties of an interacting electron system can be expressed through its electron density, while the Kohn-Sham approach makes practical calculations possible. Modern plane-wave and pseudopotential methods allow researchers to optimize structures and evaluate electronic properties with relatively high computational efficiency. Nevertheless, DFT is not a single calculation or a single level of accuracy. Results depend on the exchange-correlation functional, treatment of localized electrons, spin state, supercell size, k-point sampling, energy cutoff and other numerical choices.

For energy applications, an integrated property set is essential. A material may have a favorable band gap but poor stability, or high theoretical capacity but slow ion diffusion. A surface may strongly adsorb a reactant but bind it so strongly that product removal becomes difficult. A defect may improve conductivity but simultaneously create a recombination center. Consequently, the goal of computational materials design should be to identify a balanced set of properties rather than maximize one descriptor in isolation.

2. Computational Methods

2.1 DFT Framework and Numerical Setup

A typical calculation begins by constructing the experimental or theoretically proposed crystal structure and selecting a suitable computational cell. Geometry optimization is performed until the forces and total-energy changes satisfy convergence criteria. For slab or surface calculations, sufficient vacuum is introduced perpendicular to the surface to minimize artificial interactions between periodic images.

Plane-wave cutoffs and k-point meshes should be tested for convergence instead of being selected only from default settings.

The PBE generalized-gradient approximation is frequently used for structural optimization and initial screening. For transition-metal oxides, localized d or f electrons may require a Hubbard U correction. Hybrid functionals such as HSE06 can improve semiconductor band gaps, while GW methods can provide more advanced quasiparticle descriptions. Spin-orbit coupling should be considered for elements where relativistic effects are important. The selected method must be reported clearly because calculated band gaps, magnetic states and defect energies can change substantially with the theoretical level.

2.2 Geometry Optimization and Structural Analysis

After relaxation, lattice constants, unit-cell volume, metal-oxygen bond lengths, bond angles, coordination numbers and structural distortions are extracted. For nanomaterials, surface reconstruction and edge structures should also be inspected. The total-energy curve during relaxation provides a direct check that the optimization approaches a local energy minimum.




Figure 1. Schematic geometry-optimization curve. The minimum indicates the relaxed configuration. This is an illustrative graph, not a calculated dataset.

2.3 Stability, Formation Energy and Defect Energetics

Thermodynamic stability can be evaluated through formation energies, cohesive energies and relative energies of competing structures. Defect formation energies are especially important for oxygen vacancies, interstitials and substitutional dopants. Oxygen chemical potential must be treated consistently because vacancy stability depends on whether the system is considered under oxygen-rich or oxygen-poor conditions. For charged defects, electrostatic finite-size corrections and appropriate chemical-potential references are required.




Figure 2. Illustrative comparison of relative formation/binding energies for pristine, doped, vacancy-containing and interface models. Values are schematic only.

2.4 Electronic Structure and Band Gap

Band structures are calculated along high-symmetry paths in reciprocal space. The valence-band maximum and conduction-band minimum determine the fundamental band gap. The result can be direct or indirect depending on their positions in k-space. For energy conversion, band-edge positions are often as important as the numerical band gap because the oxidation and reduction reactions must be energetically accessible.




Figure 3. Schematic semiconductor band structure showing separated valence and conduction bands. The energy scale is illustrative.

2.5 DOS, PDOS and Chemical Bonding

Total DOS reveals the distribution of available electronic states, while PDOS identifies the contribution of particular atoms and orbitals. In many transition-metal oxides, oxygen 2p states dominate a large part of the valence band and metal d states contribute strongly near the conduction band or Fermi level. Orbital hybridization can be identified from overlapping energy regions. Charge-density difference and Bader analysis can then be used to quantify or visualize electron redistribution.




Figure 4. Schematic total DOS and projected contributions from metal d and oxygen 2p states.

2.6 Optical and Dielectric Properties

The complex dielectric function is written as $\epsilon(\omega) = \epsilon_1(\omega) + i\epsilon_2(\omega)$. The imaginary component is related to allowed electronic transitions, while the real component describes dispersive response. From these quantities, the absorption coefficient, refractive index, extinction coefficient, reflectivity and optical conductivity can be obtained. These properties are relevant to photocatalysis, photovoltaics, transparent electronics and photoelectrochemical devices.




Figure 5. Schematic optical absorption spectrum. The onset is related to electronic excitation; defect states can create additional low-energy features.

2.7 Charge Transfer and Work Function

Charge-density-difference maps show where electrons accumulate or deplete when two components interact. This is particularly useful for doped oxides, adsorbate-surface systems and heterostructures. Bader charge analysis provides a quantitative estimate of charge transfer. The work function, defined from the difference between the vacuum level and Fermi level, is useful for predicting electron emission and interfacial charge-transfer tendencies. In heterostructures, work-function mismatch can drive spontaneous charge redistribution until the interface reaches electrostatic equilibrium.




Figure 6. Schematic one-dimensional representation of charge redistribution across an oxide interface. Positive and negative regions represent illustrative accumulation/depletion.

2.8 Surface Energy and Adsorption

Surface energy is an important descriptor because nanomaterials expose a high fraction of surface atoms. Different crystallographic facets can possess different energies and reactivities. Adsorption calculations then determine how ions, atoms or molecules interact with these surfaces. The adsorption energy is commonly written as $E_{\text{ads}} = E(\text{surface+adsorbate}) - E(\text{surface}) - E(\text{adsorbate})$. More negative values generally indicate stronger binding under the chosen reference convention, but strong adsorption is not automatically synonymous with better performance.

For catalytic reactions, adsorption energies of several intermediates should be considered together. For electrochemical storage, adsorption of Li, Na, K, Mg, H or other species can be used to compare candidate sites. Geometry changes after adsorption should always be inspected because an apparently favorable energy can correspond to an unexpected structural transformation.

2.9 Ion Diffusion and NEB Calculations

The Nudged Elastic Band method is widely used to determine minimum-energy migration pathways. Several intermediate images connect an initial and final state, and the highest-energy image approximates the transition state along the calculated pathway. The migration barrier is a key descriptor for ion mobility. Low barriers generally favor fast transport, although real device behavior also depends on concentration, temperature, defects, interfaces and phase changes.




Figure 7. Schematic ion-diffusion energy profile. The peak represents the migration barrier along a minimum-energy pathway.

2.10 Magnetic, Mechanical and Phonon Properties

Spin-polarized calculations are necessary for many transition-metal oxides. Competing ferromagnetic, antiferromagnetic and ferrimagnetic arrangements can be compared through their total energies. Local magnetic moments can be obtained from site-resolved spin densities.

Mechanical properties can be evaluated from elastic constants obtained by applying small strains. Young's modulus, bulk modulus, shear modulus and Poisson's ratio can then be derived. For battery electrodes, these properties help assess resistance to deformation during ion insertion and extraction. Phonon calculations provide a test of dynamical stability; imaginary phonon frequencies may indicate structural instabilities within the selected model.




Figure 8. Illustrative stress-strain response used to explain mechanical-property analysis. The numerical values are schematic.

3. Results and Discussion

3.1 Structural Properties

The optimized structure is the starting point for interpreting all subsequent properties. A successful relaxation should produce physically reasonable coordination environments and a stable energy minimum. Calculated lattice constants can be compared with experimental values when available, but differences should be interpreted in the context of the selected functional and temperature. DFT commonly describes an idealized zero-temperature ground state, whereas experiments may include thermal expansion, defects, disorder and impurities.

In nanoscale oxides, the surface-to-volume ratio makes surface structure especially important. Under-coordinated oxygen and metal atoms can produce localized states and chemically active sites. Surface reconstruction may change the geometry enough to alter adsorption energies and catalytic pathways. Therefore, surface models should be relaxed rather than assuming that the bulk termination remains unchanged.

Structural stability is also central to electrochemical cycling. During ion insertion, local bond lengths may expand or contract and oxidation states may change. A computationally useful study should compare structures at several ion concentrations when the application involves reversible insertion. This reveals whether the material follows a smooth structural evolution or undergoes a large phase transformation.

3.2 Electronic Structure and Band Gap

The band structure determines whether the oxide is metallic, semiconducting or insulating and provides information about carrier pathways. A semiconductor with a suitable gap can absorb photons and generate electron-hole pairs. For battery electrodes, electronic conductivity is also important because charge must move through the active material during operation. However, conductivity cannot be inferred solely from the numerical band gap; carrier effective masses, defect states, orbital overlap and transport pathways also matter.

The origin of the band gap can be explored using PDOS. If oxygen p orbitals dominate the upper valence band while metal d states dominate the lower conduction band, the gap can be interpreted in terms of p-d electronic structure. In correlated transition-metal oxides, however, this simplified picture may be insufficient because localized electrons and magnetic ordering can strongly affect the states near the Fermi level.

Defects can create states inside the band gap. Oxygen vacancies may donate electronic charge or alter nearby metal oxidation states. Dopants can create shallow donor or acceptor levels or deeper localized states. The desired outcome depends on the application. For photocatalysis, controlled defect states may improve visible-light absorption, but excessive trapping can accelerate electron-hole recombination. For batteries, defect-induced conductivity may be beneficial, while excessive defect concentrations can reduce structural stability.

3.3 Density of States, Bonding and Charge Redistribution

DOS and PDOS analysis provides a microscopic explanation for changes observed in the band structure. Strong overlap between metal d and oxygen p states indicates hybridization and can be related to covalent contributions to the metal-oxygen bond. The width and position of these states can change after doping, strain or adsorption.

Charge-density difference provides complementary information. In a heterostructure, electron accumulation on one side and depletion on the other can indicate interfacial charge transfer. Such redistribution can create an internal electric field and influence the separation of photogenerated carriers. For an adsorbed ion, charge transfer can indicate whether the interaction is primarily electrostatic, covalent or mixed.

Work-function analysis is another useful descriptor. If two materials have different work functions before contact, electrons may flow when an interface forms. The resulting Fermi-level equilibration can change the band alignment and influence catalytic or photoelectrochemical behavior. Therefore, work function, charge-density difference and band alignment should ideally be analyzed together rather than independently.

3.4 Optical Properties

Optical calculations connect the electronic structure to photon absorption. The absorption edge is influenced by the fundamental electronic gap and by allowed transition matrix elements. A material may

have a nominally suitable gap but weak absorption for a particular polarization or photon-energy range. Consequently, the full calculated spectrum provides more information than the band gap alone.

Defects and dopants can introduce sub-band-gap absorption. This can be advantageous when the goal is to extend absorption toward visible wavelengths, but it can also indicate the presence of recombination centers. The interpretation should therefore consider the simultaneous effects on carrier separation, surface reaction kinetics and defect concentration.

For anisotropic crystals, the dielectric tensor can be direction dependent. This means that light polarized parallel and perpendicular to a surface can experience different absorption and refractive responses. Such anisotropy can be exploited in optical and photoelectrochemical devices.

3.5 Surface, Adsorption and Catalytic Properties

Energy conversion often occurs at surfaces rather than in the bulk. For this reason, surface termination, vacancy concentration and local coordination are essential descriptors. DFT surface calculations can identify low-energy facets and compare their adsorption properties. The most stable facet is not necessarily the most catalytically active one; synthesis conditions can stabilize metastable surfaces, and highly reactive surfaces may dominate chemical performance even when their surface energy is higher.

Catalytic mechanisms can be studied by calculating adsorption energies and, where necessary, transition states. For example, hydrogen, oxygen, water, carbon dioxide and hydroxyl-containing intermediates may interact differently with different oxide surfaces. The electronic structure of the active site determines the strength of these interactions. An optimum catalyst therefore requires balanced adsorption rather than simply the strongest possible binding.

3.6 Ion Storage and Diffusion

Metal oxides can store ions through intercalation, conversion reactions, surface adsorption or combinations of these mechanisms. DFT can compare possible ion sites and determine the energetics of different charge states or compositions. For layered oxides, interlayer spacing can provide favorable pathways, while vacancies can sometimes lower migration barriers.

The diffusion profile is particularly useful because it connects atomic structure to rate performance. A large migration barrier indicates that an ion must overcome a substantial energetic obstacle. A smaller barrier suggests easier movement, but it should not be interpreted as a guaranteed high-rate electrode because experimental transport also depends on particle size, electrolyte accessibility, concentration gradients, phase transitions and electronic conductivity.

3.7 Mechanical and Thermal Stability

An energy material must survive repeated operation. Elastic constants, stress-strain behavior, phonons and finite-temperature molecular dynamics can collectively provide information about mechanical and thermal stability. A material that is electronically attractive but mechanically fragile may fail under repeated ion insertion or thermal cycling.

For nanomaterials, interfaces can either improve or reduce mechanical stability. Strong bonding between components may transfer stress effectively, while lattice mismatch may generate strain. DFT can quantify interface binding energies and local structural distortions and can therefore guide the design of stable composite electrodes and heterostructures.

3.8 Magnetic and Spin-Dependent Properties

Magnetic oxides offer additional functionality beyond conventional energy storage. The magnetic ground state can influence electronic structure, defect formation and catalytic behavior. DFT calculations can compare several spin arrangements and determine local moments. In systems containing transition metals, a change in oxidation state during adsorption or ion insertion can also modify magnetic moments.

Although magnetism is not a required descriptor for every energy application, including it can be valuable when the oxide contains partially filled d orbitals or when multifunctional magnetic-electrochemical systems are being considered.

4. Application-Oriented Interpretation

4.1 Batteries

For lithium-, sodium- and multivalent-ion batteries, the most important computational descriptors include ion adsorption energy, theoretical capacity, voltage, diffusion barrier, electronic conductivity, formation energy and structural change during ion insertion. These properties should be evaluated together. High capacity is useful only when the host structure can reversibly accommodate the inserted species and maintain acceptable kinetics.

4.2 Supercapacitors

For supercapacitors, surface area, electronic conductivity, redox activity and ion accessibility are critical. DFT can clarify the electronic states responsible for redox activity and the preferred adsorption sites for electrolyte ions. Defects and heterostructures may increase the number of active sites, but their stability must be verified.

4.3 Photocatalysis and Water Splitting

Photocatalytic water splitting requires appropriate band-edge positions, optical absorption and efficient charge separation. DFT can calculate band structures, work functions, surface charge transfer and adsorption of water or reaction intermediates. Heterostructures are particularly attractive because interfacial charge redistribution may improve separation of electrons and holes.

4.4 Hydrogen Production and Electrocatalysis

For electrocatalytic hydrogen and oxygen reactions, adsorption free energies of relevant intermediates are important descriptors. DFT can compare pristine and defect-engineered surfaces and identify the local atomic environments responsible for favorable reaction steps. Oxygen vacancies and dopants may tune the electronic structure and alter intermediate binding.

4.5 CO₂ Conversion

CO₂ conversion requires activation of a stable molecule and stabilization of reaction intermediates. Oxide surfaces containing defects or low-coordination metal centers may provide stronger interactions with CO₂. DFT can compare adsorption geometries, charge transfer, reaction energies and transition states to determine plausible pathways.

4.6 Solar and Optoelectronic Devices

For solar and optoelectronic applications, band gap, optical absorption, dielectric response, work function, carrier effective masses and interface band alignment are important. Metal oxides are also widely used as transport layers because of their stability and tunable electronic properties. DFT-based interface calculations can help select combinations that minimize unfavorable barriers to charge extraction.

5. Effects of Doping, Oxygen Vacancies, Strain and Heterostructures

Property engineering is central to modern computational materials design. Substitutional doping can tune carrier concentration and band edges. Oxygen vacancies can change oxidation states and create localized electronic states. Strain can alter bond lengths and orbital overlap, shifting band energies and adsorption strengths. Heterostructures can generate interfacial electric fields and new charge-transfer pathways.

A scientifically strong study should calculate the energetic cost of introducing each modification rather than assuming that a defect or dopant is favorable. It should also compare multiple concentrations where practical. A single dopant configuration can be strongly dependent on the chosen supercell and may not represent the behavior of a real material at finite concentration.

6. Graphical Interpretation Guide

The figures in this article are designed to show what the major DFT plots mean. Figure 1 demonstrates the energy-minimization concept used during structural relaxation. Figure 3 shows how the band gap is read from a band structure. Figure 4 demonstrates how total DOS and orbital-resolved PDOS can be compared. Figure 5 illustrates the optical absorption response. Figure 6 represents charge transfer at an interface. Figure 7 shows how an NEB energy profile is interpreted, while Figure 8 illustrates the type of stress-strain curve used to discuss mechanical response. These are educational schematics and must not be presented as numerical results for a real material.

For a thesis or research paper based on an actual calculation, each graph should contain the material name, computational method, units, k-point path or relevant axis definition, and a caption explaining the key result. The text should then state what the graph demonstrates rather than merely describing its appearance. For example, a band-structure discussion should identify whether the gap is direct or indirect, while a DOS discussion should identify which orbitals dominate near the band edges.

7. Limitations and Scientific Considerations

DFT results are model-dependent. PBE can underestimate band gaps, while strongly correlated oxides may require DFT+U or more advanced methods. Optical calculations may omit important excitonic and many-body effects unless an appropriate treatment is used. Defect energies depend on chemical potentials, charge states and finite-size corrections. Surface calculations depend on slab thickness, termination and vacuum spacing. Diffusion barriers depend on the selected migration pathway and cell size.

Another limitation is the difference between idealized theoretical structures and experimental samples. Real nanomaterials contain disorder, impurities, grain boundaries, surface adsorbates and finite-temperature effects. Therefore, DFT should be regarded as a mechanism-discovery and materials-screening tool rather than a replacement for experiment. The strongest studies combine theoretical predictions with structural, spectroscopic, optical and electrochemical measurements.

8. Conclusion

DFT provides a comprehensive route for investigating metal oxide nanomaterials at the atomic scale and for connecting their microscopic structures with energy-related performance. A complete computational study should extend beyond a single band-gap calculation and examine a coordinated set of properties: optimized structure, lattice parameters, bond lengths and angles, formation energy, defect stability, band structure, band gap, DOS, PDOS, chemical bonding, charge transfer, work function, optical absorption, dielectric response, magnetic properties, mechanical behavior, phonon stability, surface energy, adsorption, ion diffusion and catalytic reaction energetics.

These properties address different stages of energy-material performance. Structural and thermodynamic descriptors establish stability; electronic and bonding analyses explain charge transport; optical properties determine photon interaction; surface and adsorption calculations describe chemical activity; diffusion barriers determine ion mobility; and mechanical and thermal calculations assess durability. Defects, doping, strain and heterostructures provide additional degrees of freedom for tuning these properties.

The most reliable computational design strategy is therefore multi-criteria screening. Instead of selecting a material because it has one attractive number, researchers should identify candidates that simultaneously satisfy stability, electronic, optical, ionic, mechanical and catalytic requirements for the target application. Such an approach can reduce experimental trial-and-error and accelerate the development of improved electrodes, photocatalysts, electrocatalysts and solar-energy materials. Future progress will increasingly combine DFT with high-throughput computation, machine learning and carefully controlled experiments to discover stable and efficient metal oxide nanomaterials.

9. Mathematical Equations and Worked DFT Calculations

A DFT-based research article becomes much stronger when the physical meaning of each calculated property is supported by its governing equation. The following equations provide a compact

mathematical framework for the structural, electronic, optical, surface, adsorption, diffusion, mechanical and energy-storage properties discussed above. The numerical examples are worked illustrative calculations intended to demonstrate the method; they are not claimed to be results for a particular oxide unless an actual DFT dataset is supplied.

9.1 Kohn-Sham DFT Equation

The central Kohn-Sham equation is written as:

$$[-\hbar^2/(2m) \nabla^2 + V_{\text{eff}}(r)] \psi_i(r) = \varepsilon_i \psi_i(r)$$

Here, $\hbar$ is the reduced Planck constant, m is the electron mass, ψ_i is a Kohn-Sham orbital, ε_i is its eigenvalue, and V_{eff} is the effective potential containing the external, Hartree and exchange-correlation contributions. The electron density is obtained from the occupied orbitals:

$$n(r) = \sum_i f_i |\psi_i(r)|^2$$

where f_i is the occupation of state i . In practical solid-state calculations, these equations are solved self-consistently until the electron density and total energy converge.

9.2 Total Energy and Geometry Optimization

The relaxed structure corresponds to a local minimum of the total energy with respect to atomic coordinates. The force on atom I can be expressed as:

$$F_I = -\partial E_{\text{total}} / \partial R_I$$

At convergence, the residual forces should be sufficiently small. As a simple numerical example, if the energy changes from -125.438 eV to -125.441 eV during a final relaxation step, then:

$$\Delta E = -125.441 - (-125.438) = -0.003 \text{ eV}$$

The magnitude of the energy change is therefore 0.003 eV. If the selected convergence criterion is 0.005 eV, this energy change satisfies that particular criterion. Force convergence must still be checked independently.

For a simple harmonic approximation around equilibrium, $E(x) = E_0 + k(x - x_0)^2/2$. If $k = 10 \text{ eV } \text{\AA}^{-2}$ and the displacement is $0.10 \text{ \AA}$, the energy penalty is $\Delta E = (10)(0.10)^2/2 = 0.05 \text{ eV}$. This illustrates why geometry optimization searches for the minimum-energy atomic arrangement.

9.3 Lattice Strain

The percentage strain can be calculated from the change in lattice parameter:

$$\varepsilon = [(a - a_0)/a_0] \times 100\%$$

For example, if the original lattice parameter is $a_0 = 3.80 \text{ \AA}$ and tensile strain changes it to $a = 3.88 \text{ \AA}$:

$$\varepsilon = [(3.88 - 3.80)/3.80] \times 100 = 2.105\%$$

Thus, the applied tensile strain is approximately 2.11%. The resulting band gap, bond lengths and adsorption energies can then be compared with the unstrained system.

9.4 Formation Energy

For a binary oxide M_xO_y , a simple formation-energy expression relative to elemental reference states is:

$$E_f = [E(M_xO_y) - xE(M) - (y/2)E(O_2)]/(x+y)$$

As an illustrative example, suppose $E(MO_2) = -20.0$ eV, $E(M) = -8.0$ eV and $E(O_2) = -6.0$ eV. Then:

$$E_f = [-20.0 - (-8.0) - (2/2)(-6.0)]/(1+2)$$

$$E_f = [-20.0 + 8.0 + 6.0]/3 = -6.0/3 = -2.0 \text{ eV per atom}$$

The negative value indicates that the compound is energetically favorable relative to the chosen reference states within this simplified model. In rigorous defect thermodynamics, chemical potentials and charge corrections must also be included.

9.5 Defect Formation Energy

A general charged-defect formation energy can be represented by:

$$E_f(D^q) = E_D - E_{\text{bulk}} - \sum_i n_i \mu_i + q(E_F + E_{\text{VBM}} + \Delta V) + E_{\text{corr}}$$

For an illustrative neutral oxygen vacancy, assume the defective-cell energy is -99.0 eV, the pristine-cell energy is -100.0 eV, and the oxygen chemical potential is -5.0 eV. Removing one oxygen gives $n_O = -1$ under one common sign convention, so the expression reduces to:

$$E_f(V_O) = -99.0 - (-100.0) - (-1)(-5.0) = 1.0 - 5.0 = -4.0 \text{ eV}$$

This example is intentionally simplified to show substitution into the equation. In a real study, the oxygen chemical potential is constrained by the stability region of the oxide, and the sign convention for n_i must be stated explicitly.

9.6 Band Gap Calculation

The fundamental band gap is the energy difference between the conduction-band minimum (CBM) and valence-band maximum (VBM):

$$E_g = E_{\text{CBM}} - E_{\text{VBM}}$$

If the VBM is at -0.20 eV relative to the selected zero and the CBM is at 1.80 eV, then:

$$E_g = 1.80 - (-0.20) = 2.00 \text{ eV}$$

The material therefore has an illustrative 2.00 eV band gap. If VBM and CBM occur at different k-points, the gap is indirect; if they occur at the same k-point, it is direct.

9.7 Photon Wavelength Corresponding to the Band Gap

A useful conversion between photon energy and wavelength is:

$$\lambda(\text{nm}) \approx 1240/E(\text{eV})$$

For $E_g = 2.00$ eV:

$$\lambda \approx 1240/2.00 = 620 \text{ nm}$$

Thus, a 2.00 eV optical transition corresponds to approximately 620 nm. This is only a simple energetic estimate; the actual absorption edge also depends on transition probabilities, excitonic effects and the electronic-structure method.

9.8 Adsorption Energy

Adsorption energy is commonly calculated using:

$$E_{\text{ads}} = E_{\text{surface+adsorbate}} - E_{\text{surface}} - E_{\text{adsorbate}}$$

Suppose the combined surface-plus-ion energy is -152.0 eV, the clean surface is -145.0 eV and the isolated ion reference is -6.0 eV. Then:

$$E_{\text{ads}} = -152.0 - (-145.0) - (-6.0) = -152.0 + 145.0 + 6.0 = -1.0 \text{ eV}$$

The illustrative adsorption energy is -1.0 eV, indicating favorable binding under this chosen reference convention. Different reference states can change the numerical interpretation, so the reference must always be reported.

9.9 Charge Transfer

A simple charge-transfer estimate is:

$$\Delta q = q_{\text{before}} - q_{\text{after}}$$

If an adsorbed atom has 5.0 electrons in its isolated reference and 5.7 electrons after adsorption, then:

$$\Delta q = 5.0 - 5.7 = -0.7 \text{ e}$$

The negative sign in this convention indicates that the atom gained approximately 0.7 electrons. Bader or other charge-partitioning methods should be used for actual DFT analysis, and the sign convention must be stated clearly.

9.10 Work Function

The work function is defined as:

$$\Phi = E_{\text{vacuum}} - E_F$$

If the vacuum electrostatic potential is 6.2 eV and the Fermi level is 1.7 eV on the same energy reference, then:

$$\Phi = 6.2 - 1.7 = 4.5 \text{ eV}$$

A lower or higher work function can affect interfacial electron transfer when the oxide is combined with another material.

9.11 Ion-Diffusion Barrier

The migration barrier can be estimated from the maximum energy along a minimum-energy pathway:

$$E_m = E_{\text{TS}} - E_{\text{initial}}$$

If the initial state has energy -200.0 eV and the transition state has energy -199.2 eV:

$$E_m = -199.2 - (-200.0) = 0.8 \text{ eV}$$

The illustrative migration barrier is therefore 0.8 eV. A comparison of candidate structures is meaningful when the same computational method and reference procedure are used.

For a simple Arrhenius picture, the diffusion-related rate scales approximately as $k \propto \exp(-E_m/k_B T)$. At $T=300$ K, $k_B T \approx 0.02585$ eV. For $E_m=0.50$ eV, the exponential factor is $\exp(-0.50/0.02585) \approx 4.0 \times 10^{-9}$. For $E_m=0.80$ eV, it is $\exp(-0.80/0.02585) \approx 3.7 \times 10^{-14}$. This demonstrates mathematically why even moderate changes in a migration barrier can strongly influence thermally activated transport. The prefactor and full diffusion mechanism must also be considered in real systems.

9.12 Elastic Modulus from Stress-Strain Data

In the linear elastic region, Young's modulus can be approximated by:

$$Y = \sigma/\epsilon$$

If a calculated stress is 3.0 GPa at a strain of 0.04, then:

$$Y = 3.0/0.04 = 75 \text{ GPa}$$

The illustrative Young's modulus is therefore 75 GPa. For a rigorous DFT calculation, several small positive and negative strains should be used and the slope should be obtained from a fitted stress-strain relation or from the elastic tensor.

9.13 Optical Absorption and Dielectric Function

The complex dielectric function is:

$$\epsilon(\omega) = \epsilon_1(\omega) + i\epsilon_2(\omega)$$

The absorption coefficient can be obtained from the complex refractive index. If n and k are the real and imaginary parts of the refractive index, then:

$$\alpha(\omega) = 2\omega k/c$$

For example, if $\omega = 3.0 \times 10^{15} \text{ s}^{-1}$, $k = 0.20$ and $c = 3.0 \times 10^8 \text{ m s}^{-1}$, then:

$$\alpha = [2(3.0 \times 10^{15})(0.20)] / (3.0 \times 10^8) = 4.0 \times 10^6 \text{ m}^{-1}$$

This corresponds to $4.0 \times 10^4 \text{ cm}^{-1}$ because $1 \text{ m}^{-1} = 0.01 \text{ cm}^{-1}$. The example demonstrates the unit conversion used when reporting absorption coefficients.

9.14 Theoretical Battery Capacity

A simplified theoretical specific-capacity expression is:

$$C_{\text{theoretical}} = nF/(3.6M)$$

where n is the number of electrons transferred per formula unit, F is Faraday's constant (96485 C mol^{-1}), and M is molar mass in g mol^{-1} . For an illustrative oxide with $M = 100 \text{ g mol}^{-1}$ and $n = 2$:

$$C = (2 \times 96485) / (3.6 \times 100) \approx 536.0 \text{ mAh g}^{-1}$$

This is a theoretical upper-limit-style calculation based on the assumed reaction. Real reversible capacity can be substantially lower because of incomplete utilization, structural changes, kinetics and side reactions.

9.15 Average Battery Voltage

A simplified thermodynamic relationship between reaction free energy and average voltage is:

$$\bar{V} = -\Delta G/(nF)$$

If $\Delta G = -193 \text{ kJ mol}^{-1}$ for a two-electron reaction, then:

$$\bar{V} = -(-193000) / (2 \times 96485) \approx 1.00 \text{ V}$$

The average voltage is therefore approximately 1.00 V for this illustrative reaction. In DFT studies, total-energy differences are often used as an approximation to reaction free energies, with appropriate assumptions clearly stated.

9.16 Elastic Energy and Strain

For small uniaxial strain, the elastic energy density can be approximated by:

$$U = 1/2 Y \varepsilon^2$$

Using $Y = 75 \text{ GPa}$ and $\varepsilon = 0.04$:

$$U = 0.5 \times 75 \times (0.04)^2 = 0.06 \text{ GPa}$$

Since $1 \text{ GPa} = 10^9 \text{ J m}^{-3}$, this corresponds to $6.0 \times 10^7 \text{ J m}^{-3}$. This approximation is valid only within the elastic regime.

10. How to Present the Mathematical Results in a Research Paper

For each DFT property, the recommended presentation is: (1) give the governing equation, (2) define every symbol, (3) state the computational method and convergence settings, (4) present the graph or table, (5) give the calculated value, and (6) explain its physical meaning and relevance to the target energy application. This structure prevents the results section from becoming a collection of unexplained graphs.

For example, a band-gap subsection should show the band structure, identify VBM and CBM, calculate $E_g = E_{\text{CBM}} - E_{\text{VBM}}$, state whether the gap is direct or indirect, discuss orbital contributions using PDOS, and finally connect the result to optical absorption or charge transport. Likewise, an ion-diffusion subsection should show the NEB pathway, identify the transition-state energy, calculate E_m , compare it with other structures, and explain the expected consequence for ion kinetics.

The numerical examples in this section are educational. They should be replaced by values extracted from the actual OUTCAR, vasprun.xml, QE output, or other validated DFT results before submission as a research paper. Graphs should likewise be generated from the actual calculated data rather than treating the illustrative figures in this document as experimental or first-principles measurements.

References

- Hohenberg, P., & Kohn, W. (1964). Inhomogeneous Electron Gas. *Physical Review*, 136, B864–B871.
- Kohn, W., & Sham, L. J. (1965). Self-Consistent Equations Including Exchange and Correlation Effects. *Physical Review*, 140, A1133–A1138.
- Perdew, J. P., Burke, K., & Ernzerhof, M. (1996). Generalized Gradient Approximation Made Simple. *Physical Review Letters*, 77, 3865–3868.
- Kresse, G., & Furthmüller, J. (1996). Efficiency of ab-initio total energy calculations for metals and semiconductors using a plane-wave basis set. *Computational Materials Science*, 6, 15–50.
- Kresse, G., & Furthmüller, J. (1996). Efficient iterative schemes for ab initio total-energy calculations using a plane-wave basis set. *Physical Review B*, 54, 11169–11186.
- Heyd, J., Scuseria, G. E., & Ernzerhof, M. (2003). Hybrid functionals based on a screened Coulomb potential. *Journal of Chemical Physics*, 118, 8207–8215.
- Manzeli, S., Ovchinnikov, D., Pasquier, D., Yazyev, O. V., & Kis, A. (2017). 2D transition metal dichalcogenides. *Nature Reviews Materials*, 2, 17033.
- Yu, X., Marks, T. J., & Facchetti, A. (2016). Metal oxides for optoelectronic applications. *Nature Materials*, 15, 383–396.
- Makkar, P., & Ghosh, N. N. (2021). A review on the use of DFT for the prediction of the properties of nanomaterials. *RSC Advances*, 11, 27897–27924.
- Butler, K. T., Gautam, G. S., & Canepa, P. (2019). Designing interfaces in energy materials applications with first-principles calculations. *npj Computational Materials*, 5, 19.
- Li, F., Ran, J., Jaroniec, M., & Qiao, S. Z. (2015). Solution combustion synthesis of metal oxide nanomaterials for energy storage and conversion. *Nanoscale*, 7, 17590–17610.
- An, C., Zhang, Y., Guo, H., & Wang, Y. (2019). Metal oxide-based supercapacitors: progress and perspectives. *Nanoscale Advances*, 1, 4644–4658.
- Regulation of intrinsic physicochemical properties of metal oxide nanomaterials for energy conversion and environmental detection applications. *Journal of Materials Chemistry A* (2020).
- Recent advances in engineered metal oxide nanostructures for supercapacitor applications: experimental and theoretical aspects. *Journal of Materials Chemistry A* (2021).
- Layered transition metal oxides for energy conversion and storage: a comprehensive review. *Journal of Energy Storage* (2025).